TECHNICAL DATA SHEET



HANSA CARE 8017 D Modified siloxane as an ingredient for Home and Car Care.

Description

Aminosiloxanes are Siloxanes modifed with Nitrogen groups. The modification degree lead to an

optimal performance in aqueous or solvent borne formulations for home and car care applications.

These products are excellently suited for a use in polishes, wax formulations and drying aids in automatic or manual car wash and provide for perfect drying characteristics including a good water repellence and excellent gloss.

Key Features

Water repellency, Beading effect

Durability

Enhances Gloss

Wax effect

Key Applications

Rinse Aids Car Polishes

Spray Waxes

Application

HANSA CARE 8017 D is applied as hydrophobic component with an additional gloss and smoothness in dryer formulations for automatic car wash. This makes the polymer ideal for use in formulations with wax effects. HANSA CARE 8017 D can also be used in spray wax formulations or paint polishes.

Health & Safety Health & Safety

Safety Data Sheet available on request.

Packaging

Drums and bulk containers. Please contact our sales department for more information.

Revision Date 29 Apr 2021

Revision No

Download Date 26 Apr 2024

Test **Property** Value Method

Product

Transparent, slightly Appearance opaque liquid

Chemistry **Aminosiloxane** Cationic Ionicity

MIT Free Yes Nitrogen Content (%) Approx. 1.7 Non-Volatile Content (%) Approx. 100

Nο Ultralow cyclic content Brookfield 800-4.000 cP

Addition Rates

Viscosity

0.5 - 10.0% in polishes and Dosage - 1

sealants

3.0 - 10.0% in high-gloss Dosage - 2 rinse aid formulations with

wax effect

0.5 - 5.0% in spray wax Dosage - 3

formulations

Storage

Max Storage Temperature 40 °C / 104 °F 4 °C / 39 °F Min Storage Temperature

Shelf Life 24 mths