

TECHNICAL DATA SHEET

TC-3023 30% active silicone defoamer, with Neutral pH

Description

This is a food grade silicone defoamer emulsion formulated to control foam in food systems and processes.

Key Features

- Blends easily into aqueous systems
- Excellent foam knockdown and persistence characteristics
- Effective in hot and cold systems
- Effective in low concentrations

Key Applications

- Agriculture applications, including crop spraying
- Amine scrubbing
- Oil and gas processing
- Specialty chemical formulations

Application

TC-3023 is a water dispersible 30% active silicone defoamer, with neutral pH. This antifoam is specially formulated to control foam in agriculture spraying applications.

Use and Cure Information

This product is compatible in most aqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system or dilute with process liquid prior to use. This product disperses in water systems with moderate amounts of mixing.

Health & Safety

This product is manufactured in compliance with the regulations of the U.S. Food and Drug Administration as cited in 21 CFR 173.340, defoaming agents used in processing foods. Permissible use levels for polydimethylsiloxane in food are defined by this FDA regulation. This product is approved for use in Canada under the following CFIA categories: Cleaners (Cleaners/Defoamers for washing fruits and vegetables, code C3) and Egg Treatment Compounds (Foam control compound, code LL3).

Limitations

This product is not intended for pharmaceutical use.

Revision Date 21 Sep 2021
Revision No 4
Download Date 25 Jan 2022

Property	Test Method	Value
Product		
Appearance		White liquid
Color		White
Density	BS ISO 2781	0.96-1.0 g/cm³
INCI Name		silica-filled polydimethylsiloxane
Ionicity		Non-ionic
MIT Free		No
Non-Volatile Content (%)		34
Ultralow cyclic content		No
Uncured Product		
Viscosity	Brookfield	3000 cP
Addition Rates		
Dosage - 1		100-10,000 PPM active content (Dependent on regulations specific to application)
Storage		
Max Storage Temperature		38 °C / 100 °F
Min Storage Temperature		4 °C / 39 °F
Packaging		This product is available for sale as 40 lb. pails and 441 lb. drums. and 2205 lb. totes
Shelf Life		12 mths

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time.

The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com