# TECHNICAL DATA SHEET



Method Value

Transparent liquid

0.1-1.0% by weight

This product is available for

sale as 40 lb. pails and 2205

40 °C / 104 °F

lb. totes.

Clear to amber

100 %

## **ICM 1501C** Silicone antifoam

**Property** 

Product

Color

Appearance

Solids Content (%)

Max Storage Temperature

**Addition Rates** 

Dosage - 1

Storage

Packaging

Description

CHT USA's 100% active defoamers are formulated to control foam in a wide variety of industrial processes.

**Key Features** 

Compound-free defoaming behavior with no deposition

Imparts a surface leveling effect

Effective at low dosage levels

Works in aqueous and most non-aqueous systems with some polarity

**Key Applications** 

Cloud point defoamer

Waste water treatment

Coatings

Textiles **Application** 

ICM 1501C is a non ionic silicone glycol copolymer soluble in

Shelf Life 24 mths water, alcohol and hydroalcoholic systems. ICM 1501C acts as a surface tension depressant in aqueous systems and enhances pulp drainage by decreasing air entrapment. This product has been designed

to improve dispersion and efficiency of defoaming agents. This product is used as an additive in paints and coatings where surface defects are not permitted.

#### **Use and Cure Information**

100% active silicone defoamers can be dispersed with minimal agitation in most nonaqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

### **Health & Safety**

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

This product is not intended for pharmaceutical use.

**Revision Date** 23 Feb 2024

Revision No

Download Date 19 Sep 2024