

# TECHNICAL DATA SHEET

## ACC 2028MV 20% Aminofunctional silicone microemulsion

### Description

This product is a microemulsion of a unique aminofunctional silicone. The specialized aminosilicone is designed to quickly and effectively, hydrophobe and protect a variety of automotive surfaces.

### Key Features

- Easy to formulate due to its fine particle size, which also delivers superior dilution stability
- Provides extended gloss performance in both car and furniture formulations
- Compatible with cationic, anionic, and nonionic systems
- Excellent dilution stability

### Key Applications

- Automotive car
- Mold release

### Application

ACC 2028MV is a 20% active microemulsion of a high viscosity aminofunctional silicone dispersed in water. It has been formulated with nonionic surfactants to be compatible with cationic, anionic, and nonionic systems. ACC 2028MV is designed to be use as a polish ingredient for automotive care as well as a release agent in industrial applications.

### Use and Cure Information

This microemulsion can be used directly or diluted 10:1 in water while maintaining pH less than 6, with any common acid, for optimal stability and effectiveness.

1. Thoroughly clean automotive surfaces before use.
2. Apply using a foam generating lance or spray bottle.
3. For maximum effectiveness allow to dwell for 1-2 minutes.
4. Rinse vigorously to activate.
5. Repeat applications for increased durability and effectiveness.

### Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

### Limitations

This product is not intended for pharmaceutical use.

Revision Date      22 Sep 2021  
Revision No        8  
Download Date     03 Jul 2024

### Property

#### Product

% Silicone  
Appearance  
Chemistry  
Ionicity  
pH

#### Addition Rates

Dosage - 1

#### Storage

Max Storage Temperature  
Min Storage Temperature  
Packaging  
Shelf Life

### Test Method

### Value

20 %  
Clear to slightly hazy  
Aminosiloxane Emulsion  
Non-ionic  
5.0

5-20% in industrial applications

40 °C / 104 °F  
4 °C / 39 °F

40 lb. pails or 460 lb. drums

12 mths

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com