

HANSA ADD 1060 RP

High performing superwetter for agricultural applications based on a trisiloxane backbone.

Description	Property	Test Method	Value
Silicone wetting agent for industrial agriculture applications.			
Key Features	Product		
<ul style="list-style-type: none"> World class surface tension reduction and spreading on the plant leaf. Optimized in spreading speed. Stable at pH 6-8 	Appearance		Transparent liquid
Key Applications	Chemistry		Polyether modified siloxane
<ul style="list-style-type: none"> Agricultural adjuvant Wetting and levelling agent Surface tension reduction 	Color		Colorless to slightly yellowish
Application	Density	BS ISO 2781	1,03-1,04 g/cm ³
Hansa ADD 1060 RP is commonly used as an additive in plant care formulations to improve wetting, levelling and distribution. The product can be also used as a spray tank additive to achieve the same effects.	Ionicity		non ionic
HANSA ADD 1060 RP can be added to the spray tank at a level of 0,025 - 0,100 %. In pesticide or leaf fertilizer formulations the concentration should be chosen correspondly.	Non-Volatile Content (%)		100
Health & Safety	Surface Tension		20.5 mN/m at 0.1% mN/m at 0.1%
Safety Data Sheets on request available.	Viscosity (cst)		< 100
	Storage		
	Shelf Life		24 mths

Revision Date 29 Apr 2021
 Revision No 1
 Download Date 03 Jun 2023