

## HANSA LPW 696 Concentrated silicone emulsion to be used in the leather industry

### Description

This product can be used in leather top coat to achieve a very peculiar touch. Other properties can be obtained according to the specific application.

### Key Features

- Typical silicone-soft handle
- Self-crosslinking
- Increases the surface slip thereby improving the abrasion properties of leather finishes

### Key Applications

- Any kind of leather

### Application

HANSA® LPW 696 is an concentrated emulsion of a non-ionic epoxy-functional siloxane that gives the typical soft handle of silicones to the leather.

It improves the surface slip and the abrasion properties of the leather.

It is a universal silicone that can be used in cationic and anionic ground and preground without influencing the adhesion. It can also be used in a top coat.

The aqueous emulsion HANSA® LPW 696 can be mixed with water at any ratio. The optimal application amount must be adjusted to the desired effect. We generally recommend an amount of 1 – 10 %.

### Use and Cure Information

In waterbased top coat.

### Health & Safety

Safety Data Sheets on request available.

### Packaging

Please contact our sales department for more information.

Revision Date      29 Apr 2021  
Revision No        1  
Download Date     13 Aug 2022

### Property

#### Product

Ionicity  
Silicone Yes/No  
Solids Content (%)  
pH

#### Storage

Max Storage Temperature

Shelf Life

Stability

### Test Method Value

**Non-ionic**

**Yes**

**49-52 %**

**5.5-7.0**

**40 °C / 104 °F**

**12 (if properly stored in closed original containers) mths**

**HANSA® LPW 696 is not sensitive to weak acids and alkalis. The product is sensitive to frost and in case of temperatures below the freezing point irreversible changes will occur.**

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

**CHT Germany GmbH:** Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany  
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com