TECHNICAL DATA SHEET



XAF 20 20% active water dispersible silicone antifoam

Description Property Test Method Value

in a wide variety of industrial applications. **Product Key Features**% actives

20 %

Extreme foam knockdown and defoaming persistence
 readily dispersible in aqueous systems
 Superior performance in high and low pH systems
 Outstanding performance in high and low pH Systems
 Outstanding performance in high and low pH Systems

Color
Viscosity (cst)
Off white
2000

Key Applications Storage

Coatings
 Waste water treatment
 Max Storage Temperature
 40 °C / 104 °F

Pulp and paper
Grinding applications
Packaging
Packaging
Packaging
This product is available for sale as 40 lb. pails and 441 lb.
drums, and 2205 lb. totes

Application

XAF 20 is used in to control foam in industrial applications

Shelf Life

12 mths

including, pulp and paper, oil and gas, and recycling. XAF Series Antifoams provide outstanding performance in extreme conditions including high and low pH as well as temperature extremes.

Use and Cure Information

CHT silicone antifoam emulsions can be dispearsed with minimal agitation in most aqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations:

This product is not intended for phamaceutical use.

Revision Date 23 Feb 2024

Revision No

Download Date 19 Apr 2024