

XAF 30 30% active water dispersible silicone antifoam

Description

CHT silicone antifoam emulsions are formulated to control foam in a wide variety of industrial applications.

Key Features

- Extreme foam knockdown and defoaming persistence
- readily dispersible in aqueous systems
- Superior performance in high and low pH systems
- Outstanding performance in high and low pH Systems

Key Applications

- Coatings
- Waste water treatment
- Pulp and paper
- Grinding applications

Application

XAF 30 is used in to control foam in industrial applications including, pulp and paper, oil and gas, and recycling. XAF series antifoams perform well in extreme conditions including high and low pH and temperature extremes.

Use and Cure Information

CHT silicone antifoam emulsions can be dispersed with minimal agitation in most aqueous processing applications, however it is advisable to screen each application before use. Use product as is by adding directly into foaming system, or dilute with process liquid prior to use. Effective when added prior to foam generation or when added to control existing foam.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations:

This product is not intended for pharmaceutical use.

Property

Product

% actives	30 %
Appearance	Creamy liquid
Color	Off white
Solids Content (%)	33 %
Viscosity (cst)	2500

Addition Rates

Dosage - 1	100-10,000 ppm Active
------------	-----------------------

Storage

Max Storage Temperature	40 °C / 104 °F
Shelf Life	12 mths

Revision Date	23 Feb 2024
Revision No	7
Download Date	19 Apr 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany
Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com